

# brighten



## LED MR16/MRX16 lamps

For high-output in decorative lighting applications, GE's dimmable 7-watt LED MR16/MRX16 lamp is the perfect solution.

### LOW-COST OPERATION

- For example, using only 7 watts of energy, save over \$118 in energy costs over the rated life of a lamp versus a standard 50-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus halogen MR16/MRX16 light sources

### EXCELLENT COLOR RENDERING

- Available with a CRI of 80 - 95

### COLOR TEMPERATURE

- Halogen-like color
- Available in 2700K, 3000K and 4000K

### LONG LIFE

- Up to 25,000 hours rated life (L70)

### DIMMABLE

- Dims from 100% to 10%

### BEAM PATTERNS

- Available in 15°, 25° and 35° beam patterns

### TRANSFORMER COMPATIBILITY

- A lamp-transformer compatibility table has been developed and is available at [www.gelighting.com/LED-MR16](http://www.gelighting.com/LED-MR16)

### ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

### GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: [www.led.com](http://www.led.com).

# LED MR16/MRX16 lamps

## Directional Lamps (MR16/MRX16)



Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
<b>12 Volt AC/DC MR16</b>																		
	GU5.3	6.5	75155	LED6.5XDMR16W82715	12	6	1.87	500	4900	3000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, Silver	
			75153	LED6.5DMR16W83015	12	6	1.87	520	4900	3000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, Silver	
		6.5	75158	LED6.5DMR16W84015	12	6	1.87	550	5000	4000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, Silver	
			93226	LED6.5DMR16W82725	12	6	1.79	500	2350	3000	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93222	LED6.5DMR16W83025	12	6	1.79	520	2350	2700	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93228	LED6.5DMR16W84025	12	6	1.79	550	2400	3000	82	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93227	LED6.5DMR16W82735	12	6	1.79	500	2700	3000	80	50W	25,000	Yes	★	Damp	Flood 35° beam, White	
			93223	LED6.5DMR16W83085	12	6	1.79	520	3000	2700	80	50W	25,000	Yes	★	Damp	Flood 35° beam, White	
			93229	LED6.5DMR16W84035	12	6	1.79	550	4000	2700	80	50W	25,000	Yes	★	Damp	Flood 35° beam, White	
			7	21359	LED7MRX16R930/10	12	6	2.01	350	3000	2700	95	50W	25,000	-		Damp	Spot 10° beam, Reveal
93412	LED7MR16S830/15	12	6	2.3	460	3000	3000	80	35W	25,000	Yes		Damp	Spot, 15° beam, Silver				
<b>Value 12 Volt AC/DC MR16</b>																		
	GU5.3	4.5	34560	LED4.5DMR1682735	12	6	1.78	380	1000	2700	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White	
			34561	LED4.5DMR1683035	12	6	1.78	400	1000	3000	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White	
			34563	LED4.5DMR1684035	12	6	1.78	400	1100	4000	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White	
	6.5	34606	LED6.5DMR1682725	12	6	1.78	500	2350	2700	80	50W	25,000	Yes	★	Dry	Narrow 25° beam, White		
		34607	LED6.5DMR1682735	12	6	1.78	500	1350	2700	80	50W	25,000	Yes	★	Dry	Flood, 35° beam, White		
		34611	LED6.5DMR1683025	12	6	1.78	530	2350	3000	80	50W	25,000	Yes	★	Dry	Narrow 25° beam, White		
		34625	LED6.5DMR1683035	12	6	1.78	530	1350	3000	80	50W	25,000	Yes	★	Dry	Flood, 35° beam, White		
		<b>120 Volt GU10</b>																
	GU10	3.5	37114	LED4D/GU1083035	120	6	2.1	300	550	3000	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White	
			4	89020	LED4D/GU10/NFLTP	120	3	2.1	250	720	3000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White
			6	26346	LED6D/GU10/NFL/TP	120	3	2.1	430	1100	3000	80	50W	25,000	Yes	★	Dry	Flood, 35° beam, White

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
 \*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® is a registered U.S. mark

**current**  
powered by GE

www.led.com

GE and the GE Monogram are trademarks of the General Electric Company and are used under license. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions. © 2019 Current, powered by GE

65027 (Rev. 08/01/19)