

UltraMax® General series

The UltraMax® General series electronic ballast is ideal for general long-burn applications. Full parallel operation keeps remaining lamps lit when one burns out, making management easier and reducing maintenance. Anti-striation control eliminates the maintenance issues caused by striating or spiraling lamps. And, they offer more than 90 percent efficiency.

Product Code	Old Description	New Description	Extended Description	Line Volts	# of Lamps	Lamp Type	Input Watts	Nominal Line Amps	Ballast Factor	Power Factor	Harmonic Total	Crest Factor	Minimum Starting Temp.
4 FT GENERAL ULTRAMAX INSTANT START BALLAST													
74101	GE132-N-347	GE132MAX-G-N-347	1 F32T8 120-277 N .87	347	1	F32T8	30	0.09	0.87	0.97	<=4%	<1.7%	-22° F
				347	1	F28T8	26	0.08	0.84	0.96	<=6%	<1.7%	60° F
				347	1	F32T8/25W	24	0.07	0.84	0.96	<=6%	<1.7%	60° F
72273	GE232-MV-L	GE232MAX-G-L	2 or 1- F32T8 120 to 277V L .77 BF	120-277	2	F32T8	49/48	0.42/0.18	0.79/0.77	0.99/0.98	<=8%	<1.7%	-22° F
				120-277	2	F28T8	43	0.36/0.16	0.77	0.99/0.98	<=9%	<1.7%	60° F
				120-277	2	F32T8/25W	38	0.32/0.14	0.77	0.99/0.98	<=10%	<1.7%	60° F
72275	GE232-MV-N	GE233MAX-G-N	2 or 1- F32T8 120 to 277V N .87 BF	120-277	2	F32T8	57/55	0.48/0.20	0.91/0.89	0.99/0.98	<=9%	<1.7%	-22° F
				120-277	2	F28T8	47	0.39/0.17	0.83	0.99/0.97	<=8%	<1.7%	60° F
				120-277	2	F32T8/25W	43	0.36/0.16	0.86	0.99/0.97	<=10%	<1.7%	60° F
74103	GE232-N-347	GE232MAX-G-N-347	2 or 1- F32T8 347V N .87 BF	347	2	F32T8	55	0.16	0.87	0.99	<=5%	<1.7%	-22° F
				347	2	F28T8	48	0.14	0.84	0.99	<=5%	<1.7%	60° F
				347	2	F32T8/25W	44	0.13	0.84	0.99	<=5%	<1.7%	60° F
74803	GE232MV-H	GE232MAX-G-H	2 or 1- F32T8 120 to 277V N 1.18 BF	120-277	2	F32T8	75/74	0.63/0.27	1.18	0.99/0.98	<=6%	<1.7%	-22° F
				120-277	2	F28T8	65/64	0.540/0.24	1.15/1.13	0.99/0.98	<=6%	<1.7%	60° F
				120-277	2	F32T8/25W	61/60	0.51/0.22	1.21/1.19	0.99/0.97	<=7%	<1.7%	60° F
74459	GE332MV-L	GE332MAX-G-L	3 or 2- F32T8 120 to 277V L .77 BF	120-277	3	F32T8	74/73	0.70/0.31	0.78	0.99/0.98	<=10%	<1.7%	-22° F
				120-277	3	F28T8	63	0.57/0.25	0.75	0.99/0.98	<=10%	<1.7%	60° F
				120-277	3	F32T8/25W	59	0.50/0.22	0.74	0.99/0.98	<=15%	<1.7%	60° F
74456	GE332MV-N	GE332MAX-G-N	3 or 2- F32T8 120 to 277V N .87 BF	120-277	3	F32T8	81/80	0.71/0.32	0.87	0.99/0.98	<=10%	<1.7%	-22° F
				120-277	3	F28T8	67/68	0.600/0.28	0.82	0.99/0.98	<=10%	<1.7%	60° F
				120-277	3	F32T8/25W	66/65	0.56/0.24	0.80	0.99/0.98	<=13%	<1.7%	60° F
74105	GE332-N-347	GE332MAX-G-N-347	3 or 2- F32T8 347V N .87 BF	347	3	F32T8	82	0.23	0.87	0.99	<=5%	<1.7%	-22° F
				347	3	F28T8	73	0.20	0.83	0.99	<=5%	<1.7%	60° F
				347	3	F32T8/25W	66	0.19	0.83	0.99	<=4%	<1.7%	60° F
74461	GE332MV-H	GE332MAX-G-H	3 or 2- F32T8 120 to 277V H 1.18 BF	120-277	3	F32T8	108/105	0.90/0.39	1.15	0.99	<=6%	<1.7%	-22° F
				120-277	3	F28T8	94/92	0.79/0.34	1.12	0.99/0.98	<=6%	<1.7%	60° F
				120-277	3	F32T8/25W	89/88	0.75/0.32	1.12	0.99/0.98	<=6%	<1.7%	60° F
74466	GE432MV-L	GE432MAX-G-L	4 or 3- F32T8 120 to 277V L .77 BF	120-277	4	F32T8	100/98	0.95/0.41	0.80/0.82	0.99/0.98	<=10%	<1.7%	-22° F
				120-277	4	F28T8	86/85	0.77/0.33	0.76/0.75	0.99/0.97	<=10%	<1.7%	60° F
				120-277	4	F32T8/25W	77	0.65/0.28	0.75	0.99/0.98	<=15%	<1.7%	60° F
74463	GE432MV-N	GE432MAX-G-N	4 or 3- F32T8 120 to 277V N .87 BF	120-277	4	F32T8	113/110	0.99/0.43	0.88	0.99/0.98	<=10%	<1.7%	-22° F
				120-277	4	F28T8	93/92	0.83/0.26	0.88/0.89	0.99/0.98	<=10%	<1.7%	60° F
				120-277	4	F32T8/25W	88/87	0.74/0.32	0.80	0.99/0.98	<=15%	<1.7%	60° F
74107	GE432-N-347	GE432MAX-G-N-347	4 or 3- F32T8 347V N .87 BF	347	4	F32T8	109	0.30	0.88	0.99	<=5%	<1.7%	-22° F
				347	4	F28T8	96	0.27	0.88	0.99	<=5%	<1.7%	60° F
				347	4	F32T8/25W	87	0.25	0.84	0.99	<=5%	<1.7%	60° F
67911	GE432MV-H	GE432MAX-G-H	4 or 3- F32T8 120 to 277V H 1.18 BF	120-277	4	F32T8	146/143	1.23/0.53	1.18	0.99/0.98	<=10%	<1.7%	-22° F
				120-277	4	F28T8	123/121	1.03/0.43	1.1/1.11	0.99/0.98	<=10%	<1.7%	60° F
				120-277	4	F32T8/25W	123/121	1.03/0.43	1.11	0.99/0.98	<=10%	<1.7%	60° F
8 FT GENERAL ULTRAMAX INSTANT START BALLAST													
30195	GE-159-MV-N	GE159MAX-G-N	1 F96T8 120-277V N.87 BF	120-277	1	F96T8	60/59	0.5/0.22	0.89	0.99	<=10%	<1.7%	-22° F
				120-277	1	F96T8WM	55/54	0.55/0.21	0.85	0.99	<=10%	<1.7%	60° F
				120-277	1	F96T8WMP	51	0.43/0.19		0.99	<=10%	<1.7%	60° F
74469	GE-259-MV-N	GE259MAX-G-N	2 or 1 F96T8 120-277 N BF	120-277	2	F96T8	107/105	0.90/0.38	0.88	0.99	<=7%	<1.7%	0° F
				120-277	2	F96T8WM	105/103	0.88/0.38	0.88	0.99	<=7%	<1.7%	0° F
				120-277	2	F96T8WMP	98/96	0.82/0.35	1.04	0.99	<=7%	<1.7%	0° F

Get more information at www.gelighting.com/ultramax

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied that such performance will be obtained under end-use conditions.

*Rated life is given for programmed Rapid Start ballasts. Life ratings are based on engineering data with lamps cycled every 3 or 12 operating hours.

^T8 Starcoat® Ecolux® lamp initial and mean lumen ratings reflect light output at 95°F (35°C).

