



HEIGHT OF LAMP HOLDERS FROM BASE OF FIXTURE

1.30
[32.90]

2.0 MAX
[51.1]

3.8 - 4.2
[96.5 - 106.7]
ALLOWABLE CENTER TO CENTER DISTANCE BETWEEN LAMP HOLDERS

7.4 MIN
[188.3]

WIDTH OF FIXTURE AT BASE

.7 MAX
[18]



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF
GE LIGHTING SOLUTIONS, LLC
1975 Noble Road, Bldg 338 E, East Cleveland, Ohio 44112-6300
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF GE LIGHTING SOLUTIONS, LLC IS PROHIBITED.
THIS DRAWING IS THE PROPERTY OF GE LIGHTING SOLUTIONS, LLC AND IS CONTROLLED IN A DATA MANAGEMENT SYSTEM.
DO NOT SCALE DRAWING
INTERPRET DRAWING PER ASME
14.5M 199d

UNLESS OTHERWISE SPECIFIED: UNITS ARE INCHES [mm]	
.X DECIMALS	±.2
.XX DECIMALS	±.10
.XXX DECIMALS	±.010
ANGLES	±2°
INSPECTION DIM	○
PPAP DIM	◆

DRAWING DESCRIPTION GENLYTE LUR FIXTURE DIMENSIONS				
DRAWING NUMBER	REVISION	LIFE CYCLE STATUS	SCALE 1:1	
DRAWN BY		DRAWN DATE	SIZE B	
APPROVED BY		APPROVED DATE	SHEET 1/1	