

illuminate



The bright white radiance of GE's LED lamps with light enhancing technology is not just something you see, it's something you feel.

LED A-Line A21 fully enclosed fixture lamps

Current, powered by GE offers dimmable LED A-Line lamps as an excellent option for energy savings in your fully enclosed fixtures like the Jelly Jar.

LOW-COST OPERATION

- For example, using only 12 watts of energy, save \$172 in energy costs over the rated life of the lamp versus a standard 75-watt incandescent lamp based on \$0.11 per kWh.
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent or halogen light sources

EXCELLENT COLOR RENDERING

- Available with a CRI of 80

COLOR TEMPERATURE

- Available in 3000K and 5000K

LONG LIFE

- 25,000 hours rated life (L70)

DIMMABLE

- Dims from 100% to as low as 10%

FULLY ENCLOSED

- These lamps are rated for an ambient temperature of $\geq -20^{\circ}\text{C}$ to $\leq 70^{\circ}\text{C}$ inside a fixture. They are designed for fully enclosed fixtures like the Jelly Jar.*

* Note: $\geq -20^{\circ}\text{C}$ to $\leq 70^{\circ}\text{C}$ is the rating for the ambient temperature inside an enclosed fixture. Ambient temperature outside the fixture must be $\geq -20^{\circ}\text{C}$ to $\leq 40^{\circ}\text{C}$.

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: www.LED.com


current
powered by GE

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LED A-Line A21 enclosed fixture lamps

A-Line Lamps



Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
A-21																	
	MED	12	73384	LED12A21/830FE	120	6	5.31	1100		3000	80	75W	25,000	Yes		Damp	White, Enclosed, Omni
			73404	LED12DA21/850FE	120	6	5.31	1100		5000	80	75W	25,000	Yes		Damp	White, Enclosed, Omni

Get more information at www.LED.com

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900



Product is compliant with material restriction requirements of RoHS

current
powered by GE

www.LED.com

GE and the GE Monogram are trademarks of the General Electric Company and are used under license. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2019 Current, powered by GE.

LEDL010 (Rev. 07/17/19)