

Versatile



Application illustration only, subject lamps not used in photo.



GE LED replacement lamps for HID- (Type A)

GE's LED replacement for HID lamps leverage the low energy and long life of LED. The LED lamp screws into the existing fixture without wiring or costly upgrades.

LOW-COST OPERATION

- Uses 50% less energy, providing similar light output (18,500 lumens vs. 23,500 lumens)
- For example, using 165 watts of total system energy (130W lamp and 35W ballast), save over \$1,622 in energy costs over the rated life of a lamp vs. a standard 460 watt HID lamp system (400W lamp and 60W ballast) based on \$0.11 per kWh
- Total system >100 LPW

VERSATILE UPDATE

- Omni-directional lamp utilizes existing fixture optics
- Flexible use-one lamp can be used in many types of fixtures
 - Universal burn
 - Designed to match HID ANSI profile
- Open and enclosed fixture rated options
- Temperature rating for -20°C to 50°C
- Does not work on reactor or electronic ballasts
- Exceeding temperature ratings will shorten life of lamp
- Check ballast compatibility at:
gelighting.com/led-hid-ballast-compatibility

ecomaginationSM

LONG LIFE

- 50,000 hour rated life (L70)
- Lasts 2.5X longer than HID (20,000 hrs)
- 50,000 hour rated fan life (B10)
- High-Performance fan ensures rated lamp life

COLOR RENDERING

- Available with a CRI of 70

COLOR TEMPERATURE

- Available in 4000K and 5000K
- Instant On/Brightness

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

- 5-year limited warranty
- Tether Kit included
- Robust construction with metal components


To learn more about saving money and energy, go to: <http://products.currentbyge.com>.

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

current
powered by GE



GE LED HID Type A Replacement Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Fixture Rating	Case Qty**	MOL (In)	MOD (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	^ #Location Rating	Additional Information
LED Replacement Lamps for HID																
	EX39	60	43263	LED60/2M175/740	Open and Enclosed Rated	3	8.4	4.09	8,800	4000	70	175W	50,000	-	Damp	CWA ANSI, M57, M137, M152.
			88107	LED60/2M175/750	Open and Enclosed Rated	3	8.4	4.09	8,800	5000	70	175W	50,000	-	Damp	CWA ANSI, M57, M137, M152.
		80	43258	LED80/2M250/740	Open and Enclosed Rated	3	8.4	4.09	11,800	4000	70	250W	50,000	-	Damp	CWA ANSI, M58, M138, M153.
			88099	LED80/2M250/750	Open and Enclosed Rated	3	8.4	4.09	11,800	5000	70	250W	50,000	-	Damp	CWA ANSI, M58, M138, M153.
		130	43252	LED130/2M400/740	Open and Enclosed Rated	3	8.4	4.09	18,500	4000	70	400W	50,000	-	Damp	CWA ANSI, M59, M135, M155.
			88109	LED130/2M400/750	Open and Enclosed Rated	3	8.4	4.09	18,500	5000	70	400W	50,000	-	Damp	CWA ANSI, M59, M135, M155.
		165	21259	LED165/M400/740	Open Rated	3	11.42	5.51	20,000	4000	73	400W	50,000	-	Dry	CWA ANSI, M59, M135, M155.

Energy Savings switching from HID to LED

Lamp Replacement Wattage	HID System Wattage	LED System Wattage	System Energy Savings	System Energy Cost Savings Over Life of Lamp*
400W	460W	165W	295W	\$1,622
250W	290W	112W	178W	\$979
175W	210W	88W	122W	\$671

*Based on energy rates at .11kwh over the life of the lamp

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 1

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Not suitable for air-tight explosive or hazardous fixtures.

ecomaginationSM



Product is compliant with material restriction requirements of RoHS

current
powered by GE

<http://products.currentbyge.com>

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2018 GE.



LEDL028 (Rev 06/03/18)