

Refit solutions from GE



Application illustration only, subject lamps not used in photo.

Type C LED Tubes – T5 Glass - 2' & 4'

DESCRIPTION

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

FEATURES

- T5 glass tube
- 1800-4700 lumen options available
- > 270 degree beam spread
- > 120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperature
- 50,000-hour rated life
- 5 year warranty
- UL and CUL-approved technologies
 - in compliance with UL 1598 certification

BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light –instant on
- Fully illuminates fixture - 270° light distribution
- Easy disposal, non-hazardous waste

To learn more about saving money and energy, go to: <http://products.currentbyge.com>.

ecomaginationSM

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

current
powered by GE



Product Specifications

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC*	UL	#Location Rating	Additional Information
Remote 4ft LED Glass T5 HO Tubes (Operates on Remote Driver)																
T5	G5	31	91973	LED36T5/G/4/830		20	46	4300	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91976	LED36T5/G/4/835		20	46	4400	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91977	LED36T5/G/4/840		20	46	4400	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91997	LED36T5/G/4/850		20	46	4700	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G5	31	92006	LED36T5/G/4/865		20	46	4700	6500K	80+		50,000	-	Yes	Damp	Requires Driver
Remote 2ft LED Glass T5 HO Tubes (Operates on Remote Driver)																
	G5	13	76150	LED15T5/G/2/830		20	22	1800	3000K	80+		50,000	-	Yes	Damp	Requires Driver
	G5	13	76164	LED15T5/G/2/835		20	22	1850	3500K	80+		50,000	-	Yes	Damp	Requires Driver
	G5	13	76129	LED15T5/G/2/840		20	22	1900	4000K	80+		50,000	-	Yes	Damp	Requires Driver
	G5	13	76167	LED15T5/G/2/850		20	22	1900	5000K	80+		50,000	-	Yes	Damp	Requires Driver
	G5	13	76192	LED15T5/G/2/865		20	22	1900	6500K	80+		50,000	-	Yes	Damp	Requires Driver
Remote 4ft LED Glass T5 HE Tubes (Operates on Remote Driver)																
	G5	13	34176	LED15T5/G4/830HE		20	46	1900	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G5	13	34182	LED15T5/G4/835HE		20	46	1950	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G5	13	34192	LED15T5/G4/840HE		20	46	2000	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G5	13	34194	LED15T5/G4/850HE		20	46	2000	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver
Remote 2ft LED Glass T5 HE Tubes (Operates on Remote Driver)																
	G5	8	34196	LED9T5/G2/830HE		20	22	1100	3000K	80+		50,000	-	Yes	Damp	Requires Driver
	G5	8	34197	LED9T5/G2/835HE		20	22	1150	3500K	80+		50,000	-	Yes	Damp	Requires Driver
	G5	8	34204	LED9T5/G2/840HE		20	22	1200	4000K	80+		50,000	-	Yes	Damp	Requires Driver
	G5	8	34205	LED9T5/G2/850HE		20	22	1200	5000K	80+		50,000	-	Yes	Damp	Requires Driver

Lightech Drivers - Non Dimming

GE Product Code	Description	# of Lamps
38970	LED15T8/DR/UN/2L	2

Lightech Drivers - Dimming

GE Product Code	Description	# of Lamps
38975	LED15T8/DR/4DL	4
38974	LED15T8/DR/D2L	2
92013	LED36T/DR/D4L	4
63126	LED36T8/DR/D2L	2

General Characteristics - Non Dimming

GE Product Code	38970
Output Current (A)	0.44*2
Input Watt Range (W)	30
Input Voltage (V)	120-277V
Input Frequency (Hz)	50/60Hz
Efficiency (%)	> .9%
Output Type	DC
Output Volt Range	27-33V
Dimmability	None
Ambient Temp Min	-4°F
Ambient Temp Max	113°F
Case Temperature	158°F

General Characteristics - Dimming

GE Product Code	38974	63126	38975	92013
Output Current (A)	0.44*2	1.06*2	0.44*4	1.06*4
Input Watt Range (W)	30	72	60	144
Input Voltage (V)			120-277V	
Input Frequency (Hz)			50/60Hz	
Efficiency (%)			> 90%	
Output Type			DC	
Output Volt Range			27-33V	
Dimmability			0-10V	
Ambient Temp Min			-4°F	
Ambient Temp Max			113°F	
Case Temperature			158°F	

Dimensions - Non Dimming

GE Product Code	38970
Weight	1.01
Casing Length (in)	9.5
Casing Width (in)	1.3
Casing Height (in)	1.25
Lead Exit Length (in)	26
Input Wire Length (in)	36
Output Wire Length (in)	38

Dimensions - Dimming

GE Product Code	38974	63126	38975	92013
Weight	1.01	1.08	1.08	2.15
Casing Length (in)	9.5	9.5	9.5	16.75
Casing Width (in)	1.3	1.7	1.7	2.0
Casing Height (in)	1.25	1.25	1.25	1.25
Lead Exit Length (in)	26	26	26	26
Input Wire Length (in)	36	36	36	36
Output Wire Length (in)	42	42	42	42

ecomaginationSM

current
powered by GE

<http://products.currentbyge.com>

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2018 GE.

LEDL037 (Rev. 05/02/18)



Product is compliant with material restriction requirements of RoHS

