

Refit solutions from GE



Application illustration only, subject lamps not used in photo.

Type A LED Tubes – T5 Glass - 2'- 4'

DESCRIPTION

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by an internal GE Lighttech™ driver. GE integrated LED tubes run on electronic instant-start or programmed start ballasts.

FEATURES

- T5 glass tube
- 3650-3900 lumen options available
- > 270 degree beam spread
- > 120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperature
- 50,000-hour rated life
- 5 year warranty
- UL and CUL-approved technologies
 - in compliance with UL 1598 certification

BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- Low installation cost
- No rewiring required
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light –instant on
- Fully illuminates fixture - 270° light distribution
- Easy disposal, non-hazardous waste

To learn more about saving money and energy, go to: <http://products.currentbyge.com>.

ecomaginationSM

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

current
powered by GE



Product Specifications

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
Integrated 4 ft LED Glass T5 HO Tubes (operates on Instant Start or Program Start Ballast)																
T5	G5	25.5	19203	LED26ET5/G/4/830	20	46	46	3650	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G5	25.5	19221	LED26ET5/G/4/835	20	46	46	3750	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G5	25.5	19227	LED26ET5/G/4/840	20	46	46	3800	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G5	25.5	19348	LED26ET5/G/4/850	20	46	46	3900	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G5	25.5	19488	LED26ET5/G/4/865	20	46	46	3800	6500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
Integrated 2 ft LED Glass T5 HO Tubes (operates on Instant Start or Program Start Ballast)																
	G5	11	34413	LED11ET5/G/2/830	20	22	22	1500	3000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	11	34417	LED11ET5/G/2/835	20	22	22	1550	3500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	11	34418	LED11ET5/G/2/840	20	22	22	1600	4000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	11	34424	LED11ET5/G/2/850	20	22	22	1600	5000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
Integrated 4 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)																
	G5	13	34351	LED13ET5G4/830HE	20	46	46	1900	3000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	13	34354	LED13ET5G4/835HE	20	46	46	1950	3500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	13	34355	LED13ET5G4/840HE	20	46	46	2000	4000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	13	34367	LED13ET5G4/850HE	20	46	46	2000	5000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
Integrated 3 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)																
	G5	10	34371	LED10ET5G3/830HE	20	34	34	1500	3000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	10	34376	LED10ET5G3/835HE	20	34	34	1550	3500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	10	34401	LED10ET5G3/840HE	20	34	34	1600	4000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	10	34402	LED10ET5G3/850HE	20	34	34	1600	5000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
Integrated 2 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)																
	G5	7	34403	LED7ET5/G2/830HE	20	22	22	1000	3000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	7	34404	LED7ET5/G2/835HE	20	22	22	1100	3500K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	7	34411	LED7ET5/G2/840HE	20	22	22	1150	4000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast
	G5	7	34412	LED7ET5/G2/850HE	20	22	22	1150	5000K	80+		50,000	-	Yes	Damp	Instant or PRS Ballast

ecomaginationSM



Product is compliant with material restriction requirements of RoHS

current
powered by GE

<http://products.currentbyge.com>

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2018 GE.



LEDL045 (Rev 01/24/18)