

GE Value LED Lamp Line

Every day value and performance perfect for basic LED lighting applications.



Application illustration only, subject lamps not used in photo.

NEW 50,000 hour
LED Tube



In addition to GE's premium LED Lamps, there is now a value offering with basic performance to meet the needs of ultra-competitive projects.

The offering consists of high-volume LED lamps including LED Tubes, Bright Stik™, BR30, PAR38, PAR30, MR16.

Performance at a Value
• Many Energy Star rated
• 15,000 to 50,000 hr. life






Quality & Reliability
GE branded and warrantied
offering


Ultra-Competitive
Rivals many basic performance
providers

current
powered by GE



Value LED Lamps-Product Codes and Specifications

Lamp Type	Base Type	Watts	PC	Description	Volts	Case Qty	MOL (in)	Lumens	CBCP	Color Temp.	CRI	Watt Replacement	Rated Life Hours L70	Dimmable	Energy Star	Location	Additional Info
	Med	5.5	66256	LED5.5LS3/827	120	48	4.45	450		2700	80	40W	15,000	-	★	Damp	Case = 16 3-pack
		75177	LED5.5LS3/850	120	48	4.45	450		5000	80	40W	15,000	-	★	Damp	Case = 16 3-pack	
		9	75184	LED9LS3/827	120	48	4.45	800		2700	80	60W	15,000	-	★	Damp	Case = 16 3-pack
		75588	LED9LS3/850	120	48	4.45	800		5000	80	60W	15,000	-	★	Damp	Case = 16 3-pack	
		12	75590	LED12LS2/827	120	32	4.45	1100		2700	80	75W	15,000	-	★	Damp	Case = 16 2-pack
		75591	LED12LS2/850	120	32	4.45	1100		5000	80	75W	15,000	-	★	Damp	Case = 16 2-pack	
		15	75593	LED15LS2/827	120	32	4.45	1600		2700	80	100W	15,000	-	★	Damp	Case = 16 2-pack
	75644	LED15LS2/850	120	32	4.45	1600		5000	80	100W	15,000	-	★	Damp	Case = 16 2-pack		
	MED	10	68160	LED10DR303/827W	120	6	5.4	700		2700	80	65W	25,000	Yes	★	Damp	Frosted, White body
		68161	LED10DR303/830W	120	6	5.4	700		3000	80	65W	25,000	Yes	★	Damp	Frosted, White body	
		69107	LED10DR303/850W	120	6	5.4	700		5000	80	65W	25,000	Yes	★	Damp	Frosted, White body	
		43234	LED10DR30V/827W	120	3	5.37	650		2700	80	65W	15,000	Yes	-	Damp	Frosted, White body	
		43237	LED10DR30V/830W	120	3	5.37	650		3000	80	65W	15,000	Yes	-	Damp	Frosted, White body	
	GU5.3	5.5	35542	LED5.5DMR1684035	12	6	1.8	460	1100	4000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White
		35535	LED5.5DMR1683035	12	6	1.88	420	1000	3000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White	
		35540	LED5.5DMR1682735	12	6	1.88	400	1000	2700	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White	
		7	20165	LED7XDMR16-32725	12	6	1.86	500	2350	2700	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White
		20168	LED7XDMR16-32735	12	6	1.86	500	1350	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
		20156	LED7XDMR16-38325	12	6	1.86	500	2350	3000	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
		20157	LED7XDMR16-38335	12	6	1.86	500	1350	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
	MED	12	98755	LED12DP303W83035	120	6	3.66	950	2600	3000	80	75W	25,000	Yes	★	Damp	Flood, 35° beam, White, STIR
		98811	LED12DP3L3W83035	120	6	4.61	950	2600	3000	80	75W	25,000	Yes	★	Damp	Accent, 35° beam, White, STIR	
	MED	11	91360	LED11P38W830/25	120	6	5.04	950	4000	3000	80	90W	10,000	-	-	Wet	Flood, 25° beam, White, STIR
		15	32213	LED15DP38W830/40	120	6	5.04	1300	2300	3000	81	90W	25,000	Yes	★	Wet	Flood, 40° beam, White, STIR

Lamp Type	Bulb	Watts	PC	Description	Base	QTY	MOL (in)	Initial Lumens	Color Temp.	CRI	Rated Life Hours L70	DLC	UL	Location Rating	Comments
Type A Value LED Tubes-Glass 4'															
	T8	G13	14	34283	LED14ET8/G/4/830	20	48	1950	3000K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast
		G13	14	34289	LED14ET8/G/4/835	20	48	2000	3500K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast
		G13	14	34291	LED14ET8/G/4/840	20	48	2000	4000K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast
		G13	14	34300	LED14ET8/G/4/850	20	48	2050	5000K	80+	50,000	-	Yes	Damp	Instant or PRS Ballast

current
powered by GE

<http://products.currentbyge.com>

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2019 GE.

