

Direct



Application illustration only, subject lamps not used in photo.



GE LED replacement lamps for HID-Ballast Bypass (Type B)

GE's LED replacement for HID lamps leverage the low energy and long life of LED.

The existing fixture is wired to bypass the ballast, which reduces energy use and eliminates the need to check ballast compatibility. Additional maintenance savings are realized by removing costs associated with purchasing and installing ballasts.

LOW-COST OPERATION

- Uses 50% less energy, providing similar light output
- For example, an LED lamp using 150 watts, saves \$1,705 in energy costs over the rated life of the lamp vs. a standard 460 watt HID lamp system (400W lamp and 60W ballast) based on \$0.11 per kWh
- Ballast bypass (Type B) wiring eliminates costs associated with replacing ballasts
- Total system >140 LPW

VERSATILE UPDATE

- Omni-directional lamp utilizes existing fixture optics
- Flexible use-one lamp can be used in many types of fixtures
 - Universal burn
 - Designed to match HID ANSI profile
- Rated for open and enclosed fixtures
- Temperature rating for -20°C to 50°C
- Exceeding temperature ratings will shorten life of lamp
- Type B eliminates the need to check ballast compatibility

LONG LIFE

- 2.5X Longer Life (50,000 hr LED vs 20,000 hr Metal Halide)
- 50,000 hour rated life (L70)
- 50,000 hour rated fan life (B10)
- High-Performance fan ensures rated lamp life

COLOR RENDERING

- Available with a CRI of 70

COLOR TEMPERATURE

- Available in 4000K and 5000K
- Instant On/Brightness

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient and are compliant with material restriction requirements of RoHS


GE QUALITY AND RELIABILITY

- 5-year limited warranty
- In-line fuse included
- Robust construction with metal components
- Driver with internal fuse provides 6 kV surge protection

To learn more about saving money and energy, go to: <http://products.currentbyge.com>.

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

GE LED HID Type B Replacement Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Fixture Rating	Volts	Case Qty**	MOL (In)	MOD (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	DLC	^ #Location Rating	Additional Information
LED Replacement Lamps for HID																		
	EX39	115	93101396	LED115ED28/740/347/480	Open and Enclosed Rated	347-480	3	8.3	4	18,000	4000K	>70	250W	50,000	-	Yes	Damp	Ballast bypass required.
			93101397	LED115ED28/750/347/480	Open and Enclosed Rated	347-480	3	8.3	4	18,000	5000K	>70	250W	50,000	-	Yes	Damp	Ballast bypass required.
		150	93101234	LED150ED28/740/347/480	Open and Enclosed Rated	347-480	3	8.3	4	23,500	4000K	>70	400W	50,000	-	Yes	Damp	Ballast bypass required.
			93101235	LED150ED28/750/347/480	Open and Enclosed Rated	347-480	3	8.3	4	23,500	5000K	>70	400W	50,000	-	Yes	Damp	Ballast bypass required.

Energy Savings switching from HID to LED Type B

Lamp Replacement Wattage	HID System Wattage	LED System Wattage	System Energy Savings	System Energy Cost Savings Over Life of Lamp* *Based on energy rates at .11kwh over the life of the lamp
400W	460W	150W	310W	\$1,705
250W	290W	115W	175W	\$962

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 1

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Not suitable for air-tight explosive or hazardous fixtures.

<http://products.currentbyge.com>.

current
powered by GE

GE and the GE Monogram are trademarks of the General Electric Company and are used under license. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions. © 2019 Current, powered by GE

LEDL077 (Rev 06/05/2019)

